CITY OF KELOWNA

BYLAW NO. 10696

Amendment No. 16 to Subdivision, Development and Servicing Bylaw No. 7900 - Miscellaneous Housekeeping

A bylaw to amend the "City of Kelowna Subdivision, Development and Servicing Bylaw No. 7900".

The Municipal Council of the City of Kelowna, in open meeting assembled, enacts that City of Kelowna Subdivision, Development and Servicing Bylaw No. 7900 be amended as follows:

- 1. THAT the INDEX, SCHEDULES be amended by deleting:
 - "5. City of Kelowna Construction Standards (Supplemental Standards to MMCD "GOLD" Book)
 - 6. Master Municipal Construction Documents (MMCD) 2000 Gold Book Edition (3 Volumes) Published and Available from "The Master Municipal Construction Documents Association"

And replacing it with the following:

- "5. City of Kelowna Construction Standards (Supplemental Standards to MMCD "PLATINUM" Edition Volume II, 2009)
- 6. Master Municipal Construction Documents (MMCD) 2009 Platinum Edition Volume II Published and Available from "The Master Municipal Construction Documents Association"
- 2. AND THAT SCHEDULE 4 DESIGN STANDARDS, 2. SANITARY SEWER, 2.15 Force Main, Materials, sub-paragraph (e) be amended by deleting:
 - Force main pipe must be identifiably different than water main pipe and should be white in colour (refer to supplemental specifications 5.1 Section S02732).

And replace it with:

• Force main pipe must be identifiably different than water main pipe. Refer to supplemental specifications 5.1 Section 33 34 01S.

3. AND THAT SCHEDULE 4 DRAINAGE, 3.3 MAJOR SYSTEM DESIGN, sub-section Control <u>Structures</u> be amended by adding the following after the sentence that reads "Build up of sediment shall not restrict inflows and suitable designs shall be provided to allow ease of sediment removals."

"Culvert and Bridge Capacity

The following service levels are to be used for design:

Design Flood Frequency **Road Class** Bridges, Culverts Arterial and Collector 1:200 year flood Local 1:100 year storm plus provision for overflow

if on major channel"

- 4. AND THAT SCHEDULE 4, 4. HIGHWAY be amended by deleting:
 - 4.1 General
 - 4.2 Road Classification
 - 4.3 Vertical Alignment
 - Horizontal Älignment 4.4
 - Road Cross-Section 4.5
 - 4.6 Curb and Gutter, Sidewalks and Bikepaths
 - 4.7 **Appurtenances**
 - 4.8 Pavement Structure

And replacing it with:

- 4.1 General
- 4.2 Road Classification
- 4.3 Vertical Alignment
- Horizontal Alignment Road Cross-Section 4.4
- 4.5
- Curb and Gutter, Sidewalks and Bikepaths 4.6
- 4.7 **Appurtenances**
- Pavement Structure 4.8
- **Subgrade Preparation** 4.8.1
- New Pavement Design 4.8.2
- Design of Overlays for Existing Pavements 4.8.3

- 5. AND THAT SCHEDULE 4, 5. ELECTRICAL, ELECTRICAL, STREET LIGHTING AND **COMMUNICATION WIRING**, be amended by deleting:
 - **"**5.1 General
 - Electrical
 - 5.2 5.3 Street Lighting
 - Communication Wiring" 5.4

And replacing it with:

- **"**5.1 General
- **Rules and Regulations** 5.1.1
- 5.1.2 Conduits
- 5.2 Electrical
- 5.3 Street Lighting
- 5.3.1 Design Levels
- Pole Locations 5.3.2
- Communication Wiring 5.4
- Overhead/Underground Requirements 5.5
- Kiosks/Laminate Wrapping Requirements" 5.6
- 6. AND THAT SCHEDULE 4, DESIGN STANDARDS, 7. HILLSIDE DEVELOPMENT STREET **STANDARDS** be amended by deleting:
 - 7.1 General
 - 7.2 Street Trees
 - 7.3 Hillside Street Classification
 - 7.3.1 **Arterial Streets**
 - Village Collector Streets ("Main Street") 7.3.2
 - Collector Streets 7.3.3
 - Minor Collector Streets 7.3.4
 - 7.3.5 Village Local Streets
 - 7.3.6 Local Streets
 - 7.3.7 **Public Lanes**
 - 7.3.8 Cul-de-Sac Streets and Hillside Emergency Accesses"

And replacing it with:

- 7.4 General
- 7.5 Street Trees
- Hillside Street Classification 7.6
- 7.3.1 **Arterial Streets**
- Village Collector Streets ("Main Street") 7.3.2
- 7.3.3 Collector Streets
- **Minor Collector Streets** 7.3.4
- 7.3.5 Village Local Streets
- 7.3.6 Local Streets
- 7.3.7 **Public Lanes**
- 7.3.8 Cul-de-Sac Streets and Hillside Emergency Accesses
- 7.3.9 Lighting Standards
- 7.3.10 Sanitary Sewer Location and Corridors"
- 7. AND THAT SCHEDULE 4, 7. HILLSIDE STREET STANDARDS, 7.3.8 Cul-de-Sac Streets and Hillside Emergency Accesses title be deleted and replaced with a new title ", 7.3.8 Cul-de-Sac Streets, Hillside Emergency Accesses and Hillside Private Lanes";

- 8. AND THAT SCHEDULE 4, 7. HILLSIDE STREET STANDARDS, TABLE 1 HILLSIDE STREET STANDARDS be deleted in its entirety and replaced with a new SCHEDULE 4, 7. HILLSIDE DEVELOPMENT STREET STANDARDS, TABLE 1 HILLSIDE DEVELOPMENT STREET STANDARDS as attached to and forming part of this bylaw as Appendix 'A';
- 9. AND THAT SCHEDULE 5, CONSTRUCTION DRAWINGS, Drawings Index for Reference, be amended by deleting:

Part 2b	STORM AND SANITARY SEWERS
SS-S50	Manhole Requirement for Services
SS-S51	Drainage Drywell
SS-S52	Drainage Drywell Installation
SS-S53	Pipe Perforation and Bedding Detail for Ground Water Recharge
SS-S54	Catch Basin Trapping Hood
SS-S55	Flow Control Chamber (with sediment grease trap)
SS-S56	IDF Curves
SS-S57	RipRap Design Chart

And replacing it with:

Part 2b	STORM AND SANITARY SEWERS
SS-S50	Manhole Requirement for Services
SS-S51	Drainage Drywell
SS-S52	Drainage Drywell Installation
SS-S53	Pipe Perforation and Bedding Detail for Ground Water Recharge
SS-S54	Catch Basin Trapping Hood
SS-S55	Flow Control Chamber (with sediment grease trap)
SS-S56	IDF Curves
SS-S57	RipRap Design Chart
SS-S9	Inspection Chamber for 100 to 200 Sanitary Sewer Connection

- 10. This bylaw shall come into full force and effect as of the date of adoption.
- This bylaw shall be cited as "Bylaw No. 10696, being Amendment No. 16 to Subdivision, Development and Servicing Bylaw No. 7900".

Read a first, second and third time by the Municipal Council this

Adopted by 2/3 majority of the Municipal Council of the City of Kelowna this

Mayor
-
City Clerk

APPENDIX "A"									r age i or o		
TABLE 1											
Hillside Street Standards											
	Street Conditions			Street Section Specifications							
Street Type and Condition (Std Drawing number) Max. Units Served			Design Speed ¹ (km/h)	Max. Grade (%)	ROW (m)	Street Width (m)	Parking	Curb & Gutter	Sidewalk 3	Street Trees	
	Arterial Streets >600			1	1	1	1		1		
Condition A (median) (SS-H1) within village centre where environmental conditions permit		60 (50) ⁴	8 (10) ¹¹	23.0	16.05	none permitted	barrier curb required	required both sides ⁶	required both sides and in median		
Condition B (SS-H2)	within 10-minute walking distance ⁷ of village ce within village centre where environmental con not permit the use of Condition A	ditions do	60 (50) ⁴	8 (10) ¹¹	17.0 ⁸	10.08	none permitted	barrier curb required	Required both sides ⁶	required both sides	
Condition C (SS-H3)	greater than a 10-minute walking distance ⁷ from centre.	ŭ	60 (50) ⁴	8 (10) ¹¹	15.0 ⁸	10.08	none permitted	barrier curb required	Required one side ⁶	required both sides	
Vil	Village Collector Streets (main street) 600			1	1	1	1	Ī	T	ı	
Condition A (SS-H4)	where commercial development fronts stre	eet	50	10	20.0	12.8	required on-street both sides	barrier curb required	required both sides	required both sides	
Condition B (SS-H5)	where no commercial development fronts s	street	50	10	20.0	12.8	required on-street both sides	barrier curb required	required both sides	required both sides	
Collector Streets 600											
Condition A (SS-H6)	• development ⁹ fronts both sides		50 (40) ⁴	10 (12) ¹¹	18.2 ⁸	8.68	required above curb both sides	rollover curb required	required both sides ⁶	required both sides	
Condition B (SS-H7)	development ⁹ fronts one side only		50 (40) ⁴	10 (12) ¹¹	14.9 ⁸	8.68	required above curb one side	rollover curb required ¹²	required one side ⁶	required both sides	
Condition C (SS-H8)	no development ⁹ fronts street		50 (40) ⁴	10 (12) ¹¹	14.0 ⁸	8.68	none permitted ¹⁰	rollover curb required ¹²	required one side ⁶	required both sides	
Minor Collector Streets 500											
Condition A (SS-H9)	 development⁹ fronts both sides; or, development⁹ fronts one side only 		50 (40) ⁴	10 (12) ¹¹	13.3 ⁸	7.08	required above curb one side	rollover curb required	required one side ⁶	required on one side	
Condition B (SS-H10)	no development ⁹ fronts street		50 (40) ⁴	10 (12) ¹¹	12.4 ⁸	7.08	none permitted ¹⁰	rollover curb required	required one side ⁶	required on one side	

TABLE 1 (continued) Hillside Street Standards **Street Conditions Street Section Specifications** Street Max. Design Max. ROW Street Type and Condition Width Curb & Sidewalk Speed¹ Grade **Street Trees** Units **Parking** (Std Drawing number) (m) Gutter (%) Served (km/h) (m) Village Local Streets 200 development9 fronts at least on side Village required required 40 barrier curb required both 12 8.7 17.4 on-street minimum Local $(30)^4$ required sides both sides (SS-H11) one side6 **Local Streets** 200 development⁹ fronts both sides required Condition A rollover curb optional required on 30 15 above curb 14.1 6.0 one side6 one side required (SS-H12) both sides development9 fronts one side only required rollover curb Condition B optional required on 30 15 12.3 6.0 above curb (SS-H13) required one side6 one side one side no development9 fronts street Condition C rollover curb optional required on none 30 15 10.5 6.0 $permitted^{10} \\$ one side6 one side (SS-H14) required Public Lane 10 all cases on edge of 12 rollover curb 20 6.0 5.7 (SS-H15) paved none $(15)^{11}$ required surface Hillside Emergency and Utility Vehicle Access provide a secondary access route, if possible, where a cul-de-sac exceeds maximum street length as specified by the City of 15 4.5 4.5 --Kelowna

Footnotes:

- 1. See Table 2 for alignment design criteria for each design speed.
- 2. Street width measured from curb face (gutterline).
- 3. For all conditions, sidewalks should terminate at a destination or connect with another sidewalk or trailhead.
- 4. Minimum permitted design speed reduction, where necessary due to topographic constraints, and approved by the City.
- 5. Separate left turn lanes to be provided in the medians.
- 6. Where issues of livability warrant, (eg. extreme topographic conditions) sidewalk(s) may be located in a separate dedicated corridor and street ROW width reduced accordingly. Unless necessary for pedestrian connectivity to schools, parks, commercial areas or land beyond, a sidewalk is not required for local streets accessing 30 lots or less. Street right of way may be reduced accordingly if a sidewalk is not required. (see Standard Drawings)
- 7. For this purpose, the 10-minute walking distance is considered to be ½ mile (0.8 km).
- 8. Where required, ROW and street widths will be increased at major intersections to provide for separate turning lanes.
- 9. "Development" includes all residential, mixed-use, commercial, institutional and park uses.
- 10. All parking shall be managed on-site or within small parking pullouts, as required.
- 11. Maximum grade permitted where necessary due to topographic constraints and as approved by the City.
- 12. Where no fronting development (driveway access not required), barrier curbs to be considered to restrict illegal parking on sidewalks.